

TECHNICAL DATA

Capacity under lid	0.47lt / 16oz		
Wall Thickness	Container HT16	0.40mm	0.016in
	Lid HTL115	0.30mm	0.012in
Weight (approx.) without bail	Container HT16	9.5g	0.34oz
	Lid HTL115	4.2g	0.15oz
Material	Polypropylene		
Printing	Dry Offset - Up to 6 Colours		
Colour	Available in White or Clear		

OPENING & CLOSING

TO OPEN: Peel and lift cover.

TO CLOSE: Place lid on container. Snap on then follow rim around while releasing air by pressing on center of lid to burp container. If using a closing device use proper burping function.

RECOMMENDATIONS

Do not double stack skids upon one another; racking recommended. Grade A pallets should be used with boards that have tight spacing to ensure proper box support. Stretch wrapping machine tension should be adjusted to ensure no deformation of the boxes. Hofmann recommends testing prior to full production.

APPROVALS

Virgin materials are approved for food contact and meet FDA (Food and Drug Administration USA) and HPB (Health Protection Branch Canada) regulations.

Handling conditions vary from customer to customer. Tests are recommended throughout the process of denesting, filling, conveying palletization, warehousing, transportation and utilization by intermediaries and users. Specifications can change without notice. Please contact your Hofmann representative to confirm this data.

PRODUCT CODE

CONTAINER: #HT16

LID: #HTL115 #HTL409



DIMENSIONS	CM	INCHES
Container Height	7.6	3
Container Height with Lid	11.6	4.57
Upper width with Lid	12.1	4.67
Lower Width	8.9	3.5

PACKAGING OF EMPTY PAILS & LIDS

- Warehousing of empty containers:
500 per box - 24,000 per skid
- Warehousing of Lids:
#HTL115:
500 per box - 32,000 per skid
#HTL409:
500 per box - 24,000 per skid
- Max 1 pallet high for warehousing of empty containers and lids

