

TECHNICAL DATA

Capacity under lid	3.78lt / 1.0gal		
Wall Thickness	Pail PR378	0.79mm	0.031in
	Lid LR378	1.04mm	0.041in
	Lid LR378TE	0.69mm	0.027in
Weight (approx.) without bail	Pail PR378	144g	5.08oz
	Lid LR378	44g	1.55oz
	Lid LR378TE	32g	1.13oz
Pail Material	HDPE		
Handle	Plastic optional		
Thermal range	-18°C (0°F) to 66°C (150°F)		
Printing	Dry Offset - Up to 9 colours		
Pail Colour	Standard in White, other colours available.		

TOP LOADING RESISTANCE

45kg (99lbs) at 23°C (73°F), 30 days, product temperature when filling pails and warehouse temperature will affect pail performance. Hofmann recommends testing prior to full production.

OPENING & CLOSING

TO OPEN: Break tamper evident tab, then lift cover.
TO CLOSE: Place lid on pail, press on with hands.

RECOMMENDATIONS

Do not exceed pallet edges with pails. Grade A pallets should be used with boards that have tight spacing to ensure proper pail support. To improve stability, release air from pail when applying the lid. Stretch wrapping machine tension should be adjusted to ensure no deformation of the pail. Use slip-sheet to improve pails stability. Hofmann recommends testing prior to full production.

APPROVALS

Virgin materials are approved for food contact and meet FDA (Food and Drug Administration USA) and HPB (Health Protection Branch Canada) regulations.

Handling conditions vary a lot from customer to customer. Tests are recommended throughout the process of denesting, filling, conveying palletization, warehousing, transportation and utilization by intermediaries and users. Specifications can change without notice. Please contact your Hofmann representative to confirm this data.

PRODUCT CODE

PAIL: PR378
LID: LR378 or LR378TE



DIMENSIONS

	CM	INCHES
Pail Height	19.4	7.64
Pail Height with Lid	19.5	7.68
Upper width with Lid	19.6	7.72
Lower Width	15.9	6.28

PACKAGING OF EMPTY PAILS & LIDS

- Warehousing of empty pails:
600 per tray - 1,200 per pallet
- Warehousing of Lids:
300 per box - 7,500 per pallet
- Max 2 pallets high for warehousing of pails

