

TECHNICAL DATA

Capacity under lid	0.340lt / 11.5 USoz		
Wall Thickness	Container TCR250	0.55mm	0.022in
	Lid TLR235	0.45mm	0.018in
Weight (approx.) without bail	Container TCR250	13.2g	0.46oz
	Lid TLR235	6.2g	0.22oz
Material	Polypropylene		
Thermal Range	0°C (32°F) to 90°C (194°F)		
Colour	Clear, Natural and White. Other colours available upon request.		

OPENING & CLOSING

TO OPEN: Break the Tamper-Evident tab, then remove lid.
TO CLOSE: Snap the lid at break tab area first, then follow all around while releasing air by pressing the center of the lid to burp container. If using a closing device. Use proper burping devices.

RECOMMENDATIONS

Do not double stack skids upon one another; racking recommended. Grade A pallets should be used with boards that have tight spacing to ensure proper box support. Stretch wrapping machine tension should be adjusted to ensure no deformation of the boxes. Hofmann recommends testing prior to full production.

APPROVALS

Virgin materials are approved for food contact and meet FDA (Food and Drug Administration USA) and HPB (Health Protection Branch Canada) regulations.

Handling conditions vary from customer to customer. Tests are recommended throughout the process of denesting, filling, conveying palletization, warehousing, transportation and utilization by intermediaries and users. Specifications can change without notice. Please contact your Hofmann representative to confirm this data.

PRODUCT CODE

CONTAINER: #TCR250 (8oz)

LID: #TLR235



DIMENSIONS	INCHES
Lower diameter	4.149
Upper diameter with lid on	4.55
Height with lid on	1.64

PACKAGING OF EMPTY CONTAINERS & LIDS

- Warehousing of empty containers:
500 containers per box
40 boxes per skid
20,000 containers per skid
- Warehousing of Lids:
#TLR235:
1,000 lids per box
48 boxes per skid
48,000 lids per skid

