

TECHNICAL DATA

Capacity under lid	1 US gal		
Wall Thickness	Pail PR 379	1.2mm	0.047in
	Lid LR379	0.9mm	0.035in
Weight (approx.) without bail	Pail PR 379	95.5g	3.36oz
	Lid LR379	35g	1.23oz

Pail Material Polypropylene

Handle None

Thermal range -18°C (0°F) to 38°C (100°F)

Printing Dry Offset - Up to 6 Colours

Pail Colour Standard in White, other colors available.

TOP LOADING RESISTANCE

45kg (99lb) at 23°C (73°F), 30 days, product temperature when filling pails and warehouse temperature will affect pail performance. Hofmann recommends testing prior to full production.

OPENING & CLOSING

TO OPEN: Lift snap on cover.

TO CLOSE: Place lid on pail, press on with hands.

RECOMMENDATIONS

Do not exceed pallet edges with pails. Grade A pallets should be used with boards that have tight spacing to ensure proper pail support. To improve stability, release air from pail when applying the lid. Stretch wrapping machine tension should be adjusted to ensure no deformation of the pail. Use slip-sheet to improve pails stability. Hofmann recommends testing prior to full production.

APPROVALS

Virgin materials are approved for food contact and meet FDA (Food and Drug Administration USA) and HPB (Health Protection Branch Canada) regulations.

ADVISE

Handling conditions vary a lot from customer to customer. Tests are recommended throughout the process of denesting, filling, conveying palletization, warehousing, transportation and utilization by intermediaries and users. Specifications can change without notice. Please contact your Hofmann representative to confirm this data.

PRODUCT CODE

PAIL: PR379

LID: LR379



DIMENSIONS

	CM	INCHES
Pail Height	20	8
Pail Height with Lid	20.2	8.2
Upper width with Lid	17.6	6.86
Lower Width	14.7	5.9

PACKAGING OF EMPTY PAILS & LIDS

- Warehousing of empty pails:
160 per box - 2,560 per pallet
- Warehousing of LR379 Lids:
160 per box - 5,600 per pallet

RECOMMENDATIONS

- Max 2 pallets high for warehousing of pails

