

TECHNICAL DATA

Capacity under lid	946 mL / 1 quart		
Wall Thickness	Pail PRQT	0.56mm	0.022in
	Lid LR1QT	0.81mm	0.032in
Weight (approx.) without bail	Pail PRQT	44g	1.55oz
	Lid LR1QT	18g	0.63oz
Pail Material	Polypropylene		
Handle	None		
Thermal range	-18°C (0°F) to 66°C (150°F)		
Printing	Dry Offset - Up to 9 Colours		
Pail Colour	Standard in Natural, other colors available.		

TOP LOADING RESISTANCE

45kg (99lb) at 23°C (73°F), 30 days, product temperature when filling pails and warehouse temperature will affect pail performance. Hofmann recommends testing prior to full production.

OPENING & CLOSING

TO OPEN: Lift cover.

TO CLOSE: Place lid on pail, press on with hands.

RECOMMENDATIONS

Do not exceed pallet edges with pails. Grade A pallets should be used with boards that have tight spacing to ensure proper pail support. To improve stability, release air from pail when applying the lid. Stretch wrapping machine tension should be adjusted to ensure no deformation of the pail. Use slip-sheet to improve pails stability. Hofmann recommends testing prior to full production.

APPROVALS

Virgin materials are approved for food contact and meet FDA (Food and Drug Administration USA) and HPB (Health Protection Branch Canada) regulations.

ADVISE

Handling conditions vary a lot from customer to customer. Tests are recommended throughout the process of denesting, filling, conveying palletization, warehousing, transportation and utilization by intermediaries and users. Specifications can change without notice. Please contact your Hofmann representative to confirm this data.

PRODUCT CODE

PAIL: PRQT

LID: LR1QT



DIMENSIONS

	CM	INCHES
Pail Height	12.4	4.84
Pail Height with Lid	12.4	4.88
Upper width with Lid	12.7	5.0
Lower Width	10.1	3.98

PACKAGING OF EMPTY PAILS & LIDS

- Warehousing of empty pails: 2,400 per gaylord
- Warehousing of empty pails: 300 per box - 7,200 per pallet
- Warehousing of LR1QT Lids: 240 per box - 27,000 per pallet

RECOMMENDATIONS

- Max 1 pallet high for warehousing of empty pails
- Max 2 pallets high for warehousing of lids

