

TECHNICAL DATA

Capacity under lid	11.4lt / 3gal		
Wall Thickness	Pail CR1140 Lid LCR11	1.27mm 0.86mm	0.05in 0.34in
Weight (approx.) without bail	Pail CR1140 Lid LCR11	324g 62g	11.43oz 2.19oz
Pail Material	Polypropylene		
Lid Material	HDPE		
Thermal range	-18°C (0°F) to 66°C (150°F)		
Printing	Dry Offset - Up to 6 Colours		
Pail Colour	Standard in White, other colors available.		

TOP LOADING RESISTANCE

45kg (99lbs) at 23°C (73°F), 30 days, product temperature when filling pails and warehouse temperature will affect pail performance. Hofmann recommends testing prior to full production.

OPENING & CLOSING

TO OPEN: Break tear tab, then lift cover.

TO CLOSE: Place lid on pail, press on with hands or use a rubber mallet.

RECOMMENDATIONS

Do not exceed pallet edges with pails. Grade A pallets should be used with boards that have tight spacing to ensure proper pail support. To improve stability, release air from pail when applying the lid. Stretch wrapping machine tension should be adjusted to ensure no deformation of the pail. Use slip-sheet to improve pails stability. Hofmann recommends testing prior to full production.

APPROVALS

Virgin materials are approved for food contact and meet FDA (Food and Drug Administration USA) and HPB (Health Protection Branch Canada) regulations.

Handling conditions vary a lot from customer to customer. Tests are recommended throughout the process of denesting, filling, conveying palletization, warehousing, transportation and utilization by intermediaries and users. Specifications can change without notice. Please contact your Hofmann representative to confirm this data.

PRODUCT CODE

PAIL: CR1140

LID: LCR11



DIMENSIONS	CM	INCHES
Pail Height	32	12.59
Pail Height with Lid	32.7	13.68
Upper width with Lid	25	9.85
Lower Width	21.1	8.31

PACKAGING OF EMPTY PAILS & LIDS

- Warehousing of empty pails:
360 per tray - 720 per pallet
- Warehousing of LCR11 Lids:
120 per carton - 3,600 per pallet
- Max 2 pallets high for warehousing of empty pails or lids

