

## TECHNICAL DATA

Capacity under lid	1.5L / 50.7 us oz		
Pail	PR1.5	Tamper Evident Pail with Plastic Handle	
Lid	LR1.5	Snap on Lid	
Wall Thickness	PR1.5	0.64mm	0.029in
	LR1.5	0.58mm	0.023in
Weight (approx.) without bail	PR1.5	50g	1.76oz
	LR1.5	12.5g	0.64oz
Material	PR1.5	Polypropylene	
	LR1.5	Polypropylene	
Thermal range	0°C (32°F) to 90°C (194°F)		
Decoration	Dryoffset & In Mould Labelling		
Standard Color	Standard in White, other colors available		

### TOP LOADING RESISTANCE

60kg (132lbs) at 23°C (73°F), 30 days, product temperature when filling pails and warehouse temperature will affect pail performance. Hofmann recommends testing prior to full production.

### OPENING & CLOSING

TO OPEN: Break the Tamper-Evident tab, then remove lid.

TO CLOSE: Start the lid at one side first, then apply around while releasing air on opposite side. Pressing the center of the lid if needed to burp container.

### RECOMMENDATIONS

Do not double stack skids upon one another; racking recommended. Grade A pallets should be used with boards that have tight spacing to ensure proper box support. Stretch wrapping machine tension should be adjusted to ensure no deformation of the boxes. Hofmann recommends testing prior to full production.

### APPROVALS

Virgin materials are approved for food contact and meet FDA (Food and Drug Administration USA) and HPB (Health Protection Branch Canada) regulations.

### HANDLING

Handling conditions vary from customer to customer. Tests are recommended throughout the process of denesting, filling, conveying palletization, warehousing, transportation and utilization by intermediaries and users. Specifications can change without notice. Please contact your Hofmann representative to confirm.

## PRODUCT CODE

**PAIL:** PR1.5

**LID:** LR1.5



DIMENSIONS	CM	INCHES
Lower Diameter	11.79	4.64
Upper Width with Lid	14.78	5.82
Height with Lid	13.79	5.43

### PACKAGING OF EMPTY PAILS & LIDS

- Warehousing of empty pails:
  - PR1.5 1,050 per tray
  - 1,050 per skid
  - LR1.5 720 per box (30 box per pallet)
  - 21,600 per skid
- Max 2 pallets high for warehousing of Pails
- Max 2 pallets high for warehousing of Lids

