

TECHNICAL DATA

Capacity under lid	15L / 4 US gal		
Wall Thickness	Pail CR1500	2.07mm	0.082in
	Lid LCR1700	1.9mm	0.076in
Weight (approx.) without bail	Pail CR1500	585g	20.74oz
	Lid LCR1700	160g	5.64oz

Pail Material	HDPE		
Handle	Plastic / Metal (with plastic grip)		
Thermal range	-18°C (0°F) to 66°C (150°F)		
Printing	In Mold Labelling, Dry Offset - Up to 6 Colours		
Pail Colour	Standard in White, other colors available.		

TOP LOADING RESISTANCE

60kg (132lb) at 23°C (73°F), 30 days, product temperature when filling pails and warehouse temperature will affect pail performance. Hofmann recommends testing prior to full production.

OPENING & CLOSING

TO OPEN: Break tamper evident tab, then lift cover.
TO CLOSE: Place lid on pail, press on with hands.

RECOMMENDATIONS

Do not exceed pallet edges with pails. Grade A pallets should be used with boards that have tight spacing to ensure proper pail support. To improve stability, release air from pail when applying the lid. Stretch wrapping machine tension should be adjusted to ensure no deformation of the pail. Use slip-sheet to improve pails stability. Hofmann recommends testing prior to full production.

APPROVALS

Virgin materials are approved for food contact and meet FDA (Food and Drug Administration USA) and HPB (Health Protection Branch Canada) regulations.

ADVISE

Handling conditions vary a lot from customer to customer. Tests are recommended throughout the process of denesting, filling, conveying palletization, warehousing, transportation and utilization by intermediaries and users. Specifications can change without notice. Please contact your Hofmann representative to confirm this data.

PRODUCT CODE

PAIL: CR1500
LID: LCR1700 or LCF1700



DIMENSIONS	CM	INCHES
Pail Height	32.2	12.8
Pail Height with Lid	32.4	13
Upper width with Lid	28.5	11.22
Lower Width	25	9.8

PACKAGING OF EMPTY PAILS & LIDS

- Warehousing of empty pails:
150 per tray - 288 per pallet
- Warehousing of Lids:
LCR1700: 720/1800 per pallet
LCF1700: 720 per pallet

RECOMMENDATIONS

- Max 2 pallets high for warehousing of empty pails and max 2 pallet height for lids

