

TECHNICAL DATA

Capacity under lid	8lt / 2gal		
Wall Thickness	Pail PR800	1.52mm	0.06in
	Lid LR800	1.27mm	0.05in
Weight (approx.) without bail	Pail PR800	325g	11.46oz
	Lid LR800	105g	3.7oz
Pail & Lid Material	HDPE		
Thermal range	-18°C (0°F) to 66°C (150°F)		
Printing	Dry Offset - Up to 6 Colours, In Mold Labelling		
Pail Colour	Standard in White, other colors available.		

TOP LOADING RESISTANCE

45kg (99lbs) at 23°C (73°F), 30 days, product temperature when filling pails and warehouse temperature will affect pail performance. Hofmann recommends testing prior to full production.

OPENING & CLOSING

TO OPEN: Break tear tab, then lift cover.

TO CLOSE: Place lid on pail, press on with hands or use rubber mallet.

RECOMMENDATIONS

Do not exceed pallet edges with pails. Grade A pallets should be used with boards that have tight spacing to ensure proper pail support. To improve stability, release air from pail when applying the lid. Stretch wrapping machine tension should be adjusted to ensure no deformation of the pail. Use slip-sheet to improve pails stability. Hofmann recommends testing prior to full production.

APPROVALS

Virgin materials are approved for food contact and meet FDA (Food and Drug Administration USA) and HPB (Health Protection Branch Canada) regulations.

Handling conditions vary a lot from customer to customer. Tests are recommended throughout the process of denesting, filling, conveying palletization, warehousing, transportation and utilization by intermediaries and users. Specifications can change without notice. Please contact your Hofmann representative to confirm this data.

PRODUCT CODE

PAIL: PR800

LID: LR800



DIMENSIONS

	CM	INCHES
Pail Height	24.96	9.83
Pail Height with Lid	25.19	9.92
Upper width with Lid	23.87	9.40
Lower Width	20.51	8.07

PACKAGING OF EMPTY PAILS & LIDS

- Warehousing of empty pails: 320 per tray - 640 per pallet
- Warehousing of LR800 Lids: 160 per box - 1,920 per pallet
- Max 2 pallets high for warehousing of empty pails or

