Product Specifications Tamper Evident

TECHNICAL DATA

Capacity under lid	3.78lt / 1.0gal		
Wall Thickness	Pail PR378TE Lid LR378 Lid LR378TE	1.01mm	
Weight (approx.) without bail	Pail PR378TE Lid LR378 Lid LR378TE	172g 44g 32g	6.06oz 1.55oz 1.13oz
Pail Material	HDPE		
Handle	Plastic optional		
Thermal range	-18°C (0°F) to 66°C (150°F)		
Printing	Dry Offset - Up to 9 colours		
Pail Colour	Standard in White, other colours available.		

TOP LOADING RESISTANCE

45kg (99lbs) at 23°C (73°F), 30 days, product temperature when filling pails and warehouse temperature will affect pail performance. Hofmann recommends testing prior to full production.

OPENING & CLOSING

TO OPEN: Break tamper evident tab, then lift cover. TO CLOSE: Place lid on pail, press on with hands.

RECOMMENDATIONS

Do not exceed pallet edges with pails. Grade A pallets should be used with boards that have tight spacing to ensure proper pail support. To improve stability, release air from pail when applying the lid. Stretch wrapping machine tension should be adjusted to ensure no deformation of the pail. Use slip-sheet to improve pails stability. Hofmann recommends testing prior to full production.

APPROVALS

Virgin materials are approved for food contact and meet FDA (Food and Drug Administration USA) and HPB (Health Protection Branch Canada) regulations.

Handling conditions vary a lot from customer to customer. Tests are recommended throughout the process of denesting, filling, conveying palletization, warehousing, transportation and utilization by intermediaries and users. Specifications can change without notice. Please contact your Hofmann representative to confirm this data.

PRODUCT CODE


PAIL: PR378TE LID: LR378 or LR378TE



DIMENSIONS	СМ	INCHES
Pail Height	19.17	7.55
Pail Height with Lid	19.30	7.60
Upper width with Lid	18.41	7.25
Lower Width	15.95	6.28

PACKAGING OF EMPTY PAILS & LIDS

- Warehousing of empty pails: 600 per tray - 1,200 per pallet
- Warehousing of Lids: 300 per box - 7,500 per pallet
- Max 2 pallets high for warehousing of pails





E. Hofmann Plastics Inc. • 51 Centennial Road, Orangeville, Ontario, Canada L9W 3R1 Telephone: 519-943-5050 • Toll Free: 1-877-707-Pail • Fax: 519-938-5349 • www.hofmannplastics.com

e. **HOFMANN** PLASTICS