

TECHNICAL DATA

Capacity under lid	3.80L /1.0 gal		
Wall Thickness	Pail PR380	0.88mm	0.035in
	Lid LR300	0.88mm	0.035in
Weight (approx.) without bail	Pail PR380	100g	3.53oz
	Lid LR300	38g	1.34oz

Pail Material Polypropylene

Handle None

Thermal range -18°C (0°F) to 66°C (150°F)

Printing Dry Offset - Up to 6 Colours

Pail Colour Standard in White, other colors available.

TOP LOADING RESISTANCE

45kg (99lb) at 23°C (73°F), 30 days, product temperature when filling pails and warehouse temperature will affect pail performance. Hofmann recommends testing prior to full production.

OPENING & CLOSING

TO OPEN: Lift snap on cover.

TO CLOSE: Place lid on pail, press on with hands.

RECOMMENDATIONS

Do not exceed pallet edges with pails. Grade A pallets should be used with boards that have tight spacing to ensure proper pail support. To improve stability, release air from pail when applying the lid. Stretch wrapping machine tension should be adjusted to ensure no deformation of the pail. Use slip-sheet to improve pails stability. Hofmann recommends testing prior to full production.

APPROVALS

Virgin materials are approved for food contact and meet FDA (Food and Drug Administration USA) and HPB (Health Protection Branch Canada) regulations.

ADVISE

Handling conditions vary a lot from customer to customer. Tests are recommended throughout the process of denesting, filling, conveying palletization, warehousing, transportation and utilization by intermediaries and users. Specifications can change without notice. Please contact your Hofmann representative to confirm this data.

PRODUCT CODE

PAIL: PR380

LID: LR300



DIMENSIONS	CM	INCHES
Pail Height	15.1	6
Pail Height with Lid	15.24	6.2
Upper width with Lid	20.70	8.15
Lower Width	17.83	7.02

PACKAGING OF EMPTY PAILS & LIDS

- Warehousing of empty pails:
120 per box - 2,400 per pallet
- Warehousing of LR300 Lids:
240 per box - 7,200 per pallet

RECOMMENDATIONS

- Max 2 pallets high for warehousing of pails

