

TECHNICAL DATA

Capacity under lid	4lt / 1.05gal		
Wall Thickness	Pail PR400 Lid LR53	0.88mm 0.76mm	0.035in 0.030in
Weight (approx.) without bail	Pail PR400 Lid LR53	106g 38g	3.73oz 1.34oz
Material	Polypropylene		
Handle	Optional Plastic Handle Available		
Thermal range	-18°C (0°F) to 66°C (150°F)		
Pail Colour	Standard in White, other colors available.		

TOP LOADING RESISTANCE

45kg (99lbs) at 23°C (73°F), 30 days, product temperature when filling pails and warehouse temperature will affect pail performance. Hofmann recommends testing prior to full production.

OPENING & CLOSING

TO OPEN: Break tear tab, then lift cover.

TO CLOSE: Place lid on pail, press on with hands or use rubber mallet.

RECOMMENDATIONS

Do not exceed pallet edges with pails. Grade A pallets should be used with boards that have tight spacing to ensure proper pail support. To improve stability, release air from pail when applying the lid. Stretch wrapping machine tension should be adjusted to ensure no deformation of the pail. Use slip-sheet to improve pails stability. Hofmann recommends testing prior to full production.

APPROVALS

Virgin materials are approved for food contact and meet FDA (Food and Drug Administration USA) and HPB (Health Protection Branch Canada) regulations.

Handling conditions vary a lot from customer to customer. Tests are recommended throughout the process of denesting, filling, conveying palletization, warehousing, transportation and utilization by intermediaries and users. Specifications can change without notice. Please contact your Hofmann representative to confirm this data.

PRODUCT CODE

PAIL: PR400

LID: LR53



DIMENSIONS

	CM	INCHES
Pail Height	14.73	5.80
Pail Height with Lid	14.85	5.85
Upper width with Lid	21.22	8.75
Lower Width	19.35	7.62

PACKAGING OF EMPTY PAILS & LIDS

- Warehousing of empty pails:
380 per tray - 760 per pallet
- Warehousing of LR53 Lids:
190 per box - 5,700 per pallet
- Max 2 pallets high for warehousing of empty pails or lids

