

TECHNICAL DATA

Capacity under lid 15L / 4GAL

Pail	CS1510	15L Square Pail
Lid	LSQ815	Tamper Evident Tear Strip Lid

Wall Thickness	CS1510	1.27mm	0.050in
	LSQ815	1.39mm	0.055in

Weight (approx.) without bail	CS1510	460g	16.23oz
	LSQ815	150g	5.29oz

Material	CS1510	Polypropylene
	LSQ815	HDPE

Thermal range 0°C (32°F) to 90°C (194°F)

Decoration In Mould Labelling

Standard Color Standard in White, other colors available

TOP LOADING RESISTANCE

60kg (132lbs) at 23°C (73°F), 30 days, product temperature when filling pails and warehouse temperature will affect pail performance. Hofmann recommends testing prior to full production.

OPENING & CLOSING

TO OPEN: Break the Tamper-Evident tab, then remove lid.

TO CLOSE: Start the lid at one side first, then apply around while releasing air on opposite side. Pressing the center of the lid if needed to burp container.

RECOMMENDATIONS

Do not double stack skids upon one another; racking recommended. Grade A pallets should be used with boards that have tight spacing to ensure proper box support. Stretch wrapping machine tension should be adjusted to ensure no deformation of the boxes. Hofmann recommends testing prior to full production.

APPROVALS

Virgin materials are approved for food contact and meet FDA (Food and Drug Administration USA) and HPB (Health Protection Branch Canada) regulations.

HANDLING

Handling conditions vary from customer to customer. Tests are recommended throughout the process of denesting, filling, conveying palletization, warehousing, transportation and utilization by intermediaries and users. Specifications can change without notice. Please contact your Hofmann representative to confirm.

PRODUCT CODE

PAIL: CS1510

LID: LSQ815



DIMENSIONS	CM	INCHES
Pail Height	33.55	13.21
Pail Height with Lid	34.14	13.44
Upper Width with Lid	25.46	10.02
Lower Width	21.36	8.41

PACKAGING OF EMPTY PAILS & LIDS

- Warehousing of empty pails:
 - CS1510 220 per tray
 - 440 per pallet
 - LSQ815 2,000 per pallet
- Max 2 pallets high for warehousing of Pails
- Max 2 pallets high for warehousing of Lids

