Product Specifications ST1500 + SL1500

e.HOFMANN

PLASTICS

TECHNICAL DATA			
Capacity under lid	1.5L / 52.8 us oz		
Pail	ST1500	Tamper Evident Container with Tear Tab	
Lid	SL1500	Snap on Lid	
Wall Thickness	ST1500 SL1500	0.64mm	
Weight (approx.) without bail	ST1500 SL1500	46g 1.62oz 13.8g 0.48oz	
Material	ST1500 SL1500	Polypropylene Polypropylene	
Thermal range	0°C (32°F) to 90°C (194°F)		
Decoration	In Mould Labelling		
Standard Color	Standard in White, other colors available		

TOP LOADING RESISTANCE

60kg (132lbs) at 23°C (73°F), 30 days, product temperature when filling pails and warehouse temperature will affect pail performance. Hofmann recommends testing prior to full production.

OPENING & CLOSING

TO OPEN: Break the Tamper-Evident tab, then remove lid.
TO CLOSE: Start the lid at one side first, then apply around while releasing air on opposite side. Pressing the center of the lid if needed to burp container.

RECOMMENDATIONS

Do not double stack skids upon one another; racking recommended. Grade A pallets should be used with boards that have tight spacing to ensure proper box support. Stretch wrapping machine tension should be adjusted to ensure no deformation of the boxes. Hofmann recommends testing prior to full production.

APPROVALS

Virgin materials are approved for food contact and meet FDA (Food and Drug Administration USA) and HPB (Health Protection Branch Canada) regulations.

HANDLING

Handling conditions vary from customer to customer. Tests are recommended throughout the process of denesting, filling, conveying palletization, warehousing, transportation and utilization by intermediaries and users. Specifications can change without notice. Please contact your Hofmann representative to confirm.



DIMENSIONS	СМ	INCHE
Lower Width	11.86	4.67
Upper Width with Lid	14.73	5.8
Height with Lid	11.43	4.5

PACKAGING OF EMPTY PAILS & LIDS

- Warehousing of empty pails:
 ST1500 240 per box (20 box per pallet
 4,800 per skid
 SL1500 960 per box (18 box per pallet)
- Max 2 pallets high for warehousing of Pails
- Max 2 pallets high for warehousing of Lids





