Product Specifications Heavy Duty

e.HOFMANN

PLASTICS

TECHNICAL DATA			
Capacity under lid	14lt / 4.25gal		
Lid	LR1940 - Tear Strip Optional Spout and/or Vent SLR3 - Snap on Lid		
Wall Thickness	Pail PR1400 Lid LR1940 Lid SLR3	2.29mm 1.93mm 1.93mm	0.076in
Weight (approx.) without bail	Pail PR1400 Lid LR1940 Lid LRF1920 Lid LVF1920 Lid SLR3	728g 254g 254g 254g 173g	8.96oz 8.96oz 8.96oz
Material	HDPE		
Handle	Plastic or Metal		
Thermal range	-18°C (0°F) to 66°C (150°F)		
Printing	Dry Offset - Up to 6 Colours, Heat Transfer Label, In Mold Labelling		
Pail Colour	Standard in White, other colors available.		

TOP LOADING RESISTANCE

60kg (132lbs) at 23°C (73°F), 30 days, product temperature when filling pails and warehouse temperature will affect pail performance. Hofmann recommends testing prior to full production.

OPENING & CLOSING

TO OPEN: Remove tear strip, then lift cover.

TO CLOSE: Place lid on pail, press on with hands or use a rubber mallet.

RECOMMENDATIONS

Do not exceed pallet edges with pails. Grade A pallets should be used with boards that have tight spacing to ensure proper pail support. To improve stability, release air from pail when applying the lid. Stretch wrapping machine tension should be adjusted to ensure no deformation of the pail. Use slip-sheet to improve pails stability. Hofmann recommends testing prior to full production.

APPROVALS

Virgin materials are approved for food contact and meet FDA (Food and Drug Administration USA) and HPB (Health Protection Branch Canada) regulations.

Handling conditions vary a lot from customer to customer. Tests are recommended throughout the process of denesting, filling, conveying palletization, warehousing, transportation and utilization by intermediaries and users. Specifications can change without notice. Please contact your Hofmann representative to confirm this data.

PRODUCT CODE

PAIL: PR1400

LID: LR1940, LRF1920, LFV1920, OR SLR3



DIMENSIONS	CM	INCHE
Pail Height	30	11.81
Pail Height with Lid	30.5	12.0
Upper width with Lid	31	12.21
Lower Width	26.4	10.38

PACKAGING OF EMPTY PAILS & LIDS

- Warehousing of empty pails: 180 per tray 360 per pallet
- Warehousing of LR1940 Lids:
 300 per tray 600 per pallet
 SLR3: 1200 per pallet
- Max 2 pallets high for warehousing of pails
- Max 4 pallets high for warehousing of lids







