# Product Specifications Heavy Duty

## TECHNICAL DATA

Capacity under lid	23lt / 6 gal		
Wall Thickness	Pail PR2300 Lid LR1940 Lid SLR3	1.93mm	0.076in
Weight (approx.) without bail	Pail PR2300 Lid LR1940 Lid LRF1920 Lid LVF1920 Lid SLR3:	1050g 254g 254g 254g 173g	8.96oz 8.96oz
Pail Material	HDPE		
Handle	Plastic or Metal		
Thermal range	-18°C (0°F) to 66°C (150°F)		
Printing	Dry Offset - Up to 6 Colours		
Pail Colour	Standard in White, other colors available.		

## TOP LOADING RESISTANCE

60kg (132lb) at 23°C (73°F), 30 days, product temperature when filling pails and warehouse temperature will affect pail performance. Hofmann recommends testing prior to full production.

#### **OPENING & CLOSING**

TO OPEN: Remove tear strip, then lift cover. TO CLOSE: Place lid on pail, press on with hands or use a rubber mallet.

#### RECOMMENDATIONS

Do not exceed pallet edges with pails. Grade A pallets should be used with boards that have tight spacing to ensure proper pail support. To improve stability, release air from pail when applying the lid. Stretch wrapping machine tension should be adjusted to ensure no deformation of the pail. Use slip-sheet to improve pails stability. Hofmann recommends testing prior to full production.

#### APPROVALS

Virgin materials are approved for food contact and meet FDA (Food and Drug Administration USA) and HPB (Health Protection Branch Canada) regulations.

#### ADVISE

Handling conditions vary a lot from customer to customer. Tests are recommended throughout the process of denesting, filling, conveying palletization, warehousing, transportation and utilization by intermediaries and users. Specifications can change without notice. Please contact your Hofmann representative to confirm this data.

# PRODUCT CODE

**PAIL:** PR2300

LID: LR1940, LRF1920, LFV1920, OR SLR3




DIMENSIONS	СМ	INCHES
Pail Height	44	17.32
Pail Height with Lid	44.3	17.44
Upper width with Lid	31	12.21
Lower Width	26.3	10.35

## PACKAGING OF EMPTY PAILS & LIDS

- Warehousing of empty pails: 180 per pallet
- Warehousing of LR1940 Lids: 300 per tray - 600 per pallet SLR3: 1200 per pallet

## RECOMMENDATIONS

- Max 4 pallets high for warehousing of empty pails
- Max 4 pallets high for warehousing of lids





E. Hofmann Plastics Inc. • 51 Centennial Road, Orangeville, Ontario, Canada L9W 3R1 Telephone: 519-943-5050 • Toll Free: 1-877-707-Pail • Fax: 519-938-5349 • www.hofmannplastics.com

# e. **HOFMANN** PLASTICS